

TAILOR-MADE CAR SEAT COVERS

Set of covers for two front seats and single passenger seats



PRODUCER: AUTO-DEKOR sp. z o.o. sp.k.

ul. Spółdzielcza 4, 38-420 Korczyna, Poland e-mail: kontakt@autodekor.pl





WARNING! use the product only for its intended purpose. Any modifications to the product is prohibited. The product is not a toy.



Before installing and using the product, it is important to read the documentation on the safe use and installation of the product.



INSTALLATION MANUAL



SAFE INSTALLATION AND SAFE USE MANUAL

tailor-made covers
Set of covers for two front seats and single passenger seats

NOTE! Please read the safety instructions and the installation manual supplied before starting the installation.

Ensure your safety and that of your passengers by following the guidelines in

AUTO-DEKOR car seat covers are designed and manufactured specifically for certain car makes and models. They should only be used in compatible

Cars.

The manufacturer/seller is not responsible for any direct or indirect damage or adverse consequences resulting from improper use of the products.

Car seat covers should be fitted directly onto the original car upholstery. It is essential car upholstery of the products of the products of the products of the products. to remove any previously used car seat protection, such as old covers or car seat protectors, etc., to ensure the correct functioning of the AIRBAG seams, which are key to the safety of the product. Only fit the covers as specified on:

- · Headrests · Other upholstery depending on the model and configuration of your car (e.g., additional armrests). 2. Eye protection:

To reduce the risk of injury, wear safety goggles when fitting the covers or have them fitted by a qualified vehicle service centre.

Installation instructions:
 Install the covers according to the instructions supplied.

Ensure that the covers are correctly fitted to the seats, paying particular attention to the operation of the airbag system (see item 4), seat belts and other safety systems in the seats of your car.

Only correct installation of the covers will ensure durability, enhance the aesthetics of

the interior and allow the correct operation of the airbags. Incorrect installation may affect the safety, comfort and durability of the product. . Airbag compatibility

4. Airbag compatibility
NOTE: Incorrect installation may prevent the seat airbags from deploying correctly in the event of a collision, posing a serious risk to your safety!
The covers are designed to be compatible with airbag systems (AIRBAG). Where airbags are present, the covers have a special seam that breaks when the airbags deploy without delaying them. As a result, the covers are suitable for both cars with

airbags are present, the covers raive a special searn that oreas when the airbags deploy without delaying them. As a result, the covers are suitable for both cars with and without airbags.

The solution has been tested by TÜV NORD Polska Sp. z o.o. and certified with the TÜV "Product Tested" safety mark.

Ensure that the covers are installed correctly and do not obstruct the airbag areas. Strict adherence to the installation instructions is essential for the correct functioning of the airbags in the event of an accident.

For seats equipped with side airbags, the side of the cover with the AIRBAG label must be fitted to the side of the seat where the airbag is located. Ensure that the special seam on the cover is aligned with the original seam on the seat.

Correct and careful installation of the covers is essential for full side airbag compatibility.

Regularly inspect the covers to ensure that they are secure and do not move while driving. Check that the AIRBAG seam is correctly positioned. If you notice the covers shifting or not fitting properly, adjust them immediately. Do not use covers that are damaged or do not fit these seats.

5. Compatibility with heated seats:

AUTO-DEKOR covers are compatible with seat heating functions. Ensure that the covers do not obstruct or cover the seat heating controls. Do not use the covers if they are damaged or if there are problems with the heating functions.

6. Compatibility with ventilated seats:

AUTO-DEKOR covers are not compatible with the backrest and seat ventilation functions. If your vehicle has ventilated seats, please note that their performance may be reduced when using the covers.

7. Avoid blocking vehicle systems:

Ensure that the covers do not block air vents, seat ventilation systems or seat adjustment mechanisms, as this may affect their operation and safety.

8.Regular inspections:

Inspect the covers regularly to ensure that they are securely fastened and do not move while driving. Check that the AIRBAG seam is in the correct position and that the covers do not interfere with seat belts, safety systems or other seat mechanisms. Periodically inspect the covers for damage such as tears, abrasions or general wear and tear. If damage is found, always replace the upholstery to ensure safety and

The covers are not toys. Ensure that children and pets do not play with the covers or fasteners as this may cause choking or injury. Keep the outer packaging away from small children (risk of strangulation).

10.Warning – hot surfaces:
Avoid contact between the covers and hot surfaces, such as the car body or air vents,

as this may deform or damage the material. Avoid fire. The covers are not fireproof. Keep them away from heat sources, naked

Hands and cigarettes.

11. Cleaning and maintenance:
Clean the covers according to the instructions on the product label, using a damp cloth and mild detergent. Avoid strong chemicals that may damage the material.
Ensure that the covers are completely dry before use.

12. Storage:
Store the covers in a cool, dry place when not in use to prevent damage. Avoid exposure to direct sunlight which may cause fading.

exposure to orrect sunignt which may cause racing.

13. Disposal:
If you need to replace or dispose of the product, follow your local waste disposal guidelines. The product may be recyclable at designated collection points.

14. The product is manufactured in Poland in accordance with European Union regulations.

15. For questions, incident reports or recall information, please contact the manufacturer.

Manufacturer:
AUTO-DEKOR sp. z o.o. sp.k., ul. Spółdzielcza 4, 38-420 Korczyna, Poland. phone no. +48 13 43 898 101, email: kontakt@autodekor.pl



INSTALLATION MANUAL

tailor-made covers Set of covers for two front seats and single passenger seats

read the following installation manual and the safety instructions d before starting the installation.

Ensure the car is parked on level ground and the engine is switched off before starting the installation. Apply the handbrake for added safety.

Always wear safety goggles when fitting the covers to reduce the risk of injury!

Remove any previously used car seat protection, such as old covers or car seat protectors, etc. Remove any sharp objects (e.g., keys, pens, tools) from the seats to prevent damage during installation. Thoroughly clean the seats thoroughly to remove dust, dirt, and debris for better adhesion of the covers.

Only fit the covers as intended on: front seats, passenger seats in rear rows, headrests, other upholstery depending on the car model and configuration (e.g., additional armrests). Only correct installation of the covers will ensure durability, enhance the aesthetics of the interior and allow the correct operation of the airbags.

1. Front seats, single seats: Remove the headrest from the seat. If the headrest cannot be removed, the cover may have a Veloro hole. Open the Velcro strap on the cover wide and slide it over the headrest, starting from either side. Depending on the configuration of your car, the seatback may have pockets or tables (Fig. 5). In this case, the covers may have zip fasteners that allow access to these integrated features.

(Fig. 5). In this case, the covers may mave approximate. In integrated features. For seats with tables, at the very beginning of the installation, open the zip fasteners on the opposite sides of the cover along the line of the table. Then pull the table through the hole and push the zip fasteners up to secure them in the place where the table is fixed to the backrest (Fig. 5), ensuring that the cover fits securely and does not interfere with its function. Once this is done, continue to fit the covers. Access to the pockets is easy thanks to a hole with two zip fasteners that can be

opened if necessary (Fig. 5). These design features make the covers suitable for

seats with or without tables and pockets.

Next, place the top of the cover evenly over the seat, starting at the top and working your way down. Make sure that the cover conforms to the shape of the stretching if necessary to ensure a secure fit over the original upholstery (Fig. 1).

stretching in necessary to ensure a secure int over the original upnoistery (Fig. 1). The front seat covers are designed to be compatible with airbag systems (AIRBAG) in the front seats. Where airbags are present, the covers have a special seam (Fig. 2) that breaks when the airbags deploy without delaying them. As a result, the covers are suitable for both cars with and without airbags. The solution has been tested by TUV NORD Polska Sp. z o.o. and certified with the TÜV "Product Tested" safety mark. For seats equipped with side airbags, the side of the cover with the AIRBAG label (Fig. 2) must be fitted to the side of the seat where the airbag is located, also aligning the special seam on the cover with the original seam on the seat

Correct and careful installation of the covers is essential for full side airbag compatibility.

Next, pull the component equipped with the elastic loops (Fig. 2, Fig. 4a, 4b) from the inside of the cover through the gap between the seat and the seatback so that it is visible from the back of the car seat. Later, this will allow the elastic loops to be attached to the structure at the bottom of the seat, providing stability for the cover.

Next, place the lower part of the cover over the seat, carefully adjusting it to fit the

Once the entire cover is in place, start to secure it.

Once the entire cover is in place, start to secure it.

The covers have all the necessary holes to accommodate design components such as headrests, handles, or backrest adjustment mechanisms. Place them carefully under the plastic trim of the original components (Fig. 1), e.g., using a small

Cateriury under the prastic units and consistent of the seats. If your headrest cannot be removed, fasten the Velcro strap that you have just undone around the headrest, leaving small sections of it undone at the headrest mounting holes. You can also insert these sections under the plastic trim of the original holes, e.g., using a small screwdriver.

Finally, proceed with securing the cover. At this stage, stretch and secure the rectangular component you have pulled between the seat and the seatback. Make any final adjustments to ensure that the cover is correctly aligned and taut. This will ensure that the cover atheres neatly and securely to the seat.

When making final adjustments, check that the AIRBAG seam is in the correct position. If you notice the covers shifting or not fitting properly, adjust them immediately.

There are two ways of securing the cover: The first way is to attach the elastic loops using special hooks (Fig. 3a). Secure the elastic loops with hooks by attaching them to the loops on the opposite side, springs, ho

The second way is to pull the supplied cord (Fig. 3b) through all the elastic loops of the mounted cover. Once this is done, tighten the cord and tie it off so that it forms a loop that connects all the small loops (Fig. 4b). Be sure to trim any excess cord.

NOTE:


- Do not attach the elastic loops or the straps to the sliding seat guides!

- Always wear safety goggles when fitting the covers, especially the hooks, to reduce the risk of injury!

2. Installation of covers on individual seats in the second and third rows If your car has single seats in the second and third rows, install the covers intended for them in the same way as you did on the front seats. This process is described in section 1. If the seats in the rear rows can be tilted or lifted, use this function during installation. This will help provide better access to the seats, especially the lower part, during the final stage of fitting the covers.

stallation of headrest, armrest and other upholstery covers t the covers for the headrests, armrests, and other upholstery by carefully retching them over each component, ensuring they are properly aligned and taunt (Fig. 2). NOTE: Do not secure headrest or armrest covers with hooks!

















certyfikat.tuv-nord.9

ELEGANCE, PREMIUM line products